

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** LeuchtenDirekt

**Supplier's address:** -

**Model identifier:** E0001676 (997437)

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	-		
Mains or non-mains:	MLS	Connected light source (CLS):	Nein
Colour-tuneable light source:	Ja	Envelope:	-
High luminance light source:	Nein		
Anti-glare shield:	Nein	Dimmable:	Yes


## Product parameters

Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	2	Energy efficiency class	E
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	180 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power ( $P_{on}$ ), expressed in W	1,5	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,39
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without	Height	Spectral power distribution in the	See image in last page
	Width		
	Depth		

separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,439 0,400
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	7	Survival factor	1,00
the lumen maintenance factor	0,96		
<b>Parameters for LED and OLED mains light sources:</b>			
displacement factor (cos $\phi_1$ )	0,87	Colour consistency in McAdam ellipses	5
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,8	Stroboscopic effect metric (SVM)	0,3

(a): not applicable;

(b): not applicable;



**LED Akku Pendelleuchte David in Schwarz 1,50W 180lm IP44**

Campinglampen


UVP: 140,90 Euro

Haben Sie eine Frage zum Produkt?  
info@click-licht.de  
(+49) 2361 40 67 600  
Montag - Freitag 09:00 - 16:00 Uhr



<b>Artikelnummer</b>	A-415506
<b>Material</b>	Metall
<b>Farbe</b>	Schwarz
<b>Anschlussspannung</b>	5 V
<b>Leistungsaufnahme</b>	1.5 W
<b>Schutzklasse</b>	III
<b>Schutzart</b>	IP44
<b>Montageart</b>	Decke
<b>Dimmbar</b>	Ja
<b>Dimmart</b>	Fernbedienung
<b>Lichttechnologie</b>	LED
<b>Bauform</b>	LED-Platine
<b>Farbtemperatur</b>	RGBW
<b>Lichtfarbe</b>	Goldweiß
<b>Lichtstrom</b>	180 lm
<b>Farbwiedergabeindex</b>	> 80
<b>Lebensdauer</b>	25000 h
<b>Schaltzyklen</b>	15000
<b>Startzeit</b>	1 s
<b>Abstrahlwinkel</b>	120 Grad
<b>Anwendungsbereich</b>	Garten, Balkon, Terrasse
<b>Stil</b>	Zeitlos
<b>Form</b>	rund


Art-Nr. A-415506

 Diese Leuchte enthält eingebaute LED-Lampen.

**A++**  
**A+**  
**A**  
**B**  
**C**  
**D**  
**E**

} LED

Die Lampen können in der Leuchte nicht ausgetauscht werden.

874/2012 

<b>Netzstecker</b>	Nein
<b>Schalter</b>	Ja
<b>Touchfunktion</b>	Ja
<b>Leuchtmittel</b>	Ja, fest verbaut
<b>Touch</b>	Ja
<b>Produktmaße</b>	(H) 290 mm (Ø) 460 mm
<b>Produktgewicht</b>	0.9 kg