

NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A

Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE

Model identifier: 9333063

Type of light source: LED



Product information Sheet

General Information

Material number	9333063
Type	Pendant lamp
Product segment	INDOOR

Dimensions

Diameter (in cm)	80 Cm
Width (in cm)	
Height (in cm)	150 Cm
Net Weight	13.5 Kg

Material & Colour

Enclosure Material	Metal & Crystal
Colour	Sandy Gold
Adjustable	Yes

Functionality

Switch Type	
Function	Triac Dimmable
Battery	
USB Charger	

Technical Information


Protection Degree	IP20
Protection Class	I
Mains Voltage	230V
max. Wattage	72W
Lumen	6351Lm
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3500K
Nominal Lifetime (in h)	30000H
Switching Cycles	-
Colour Rendering Index (Ra, CRI)	>80
Rated Lamp Power (0,1W precision)	
Colour Tolerance (LED, SDCM)	<6

Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	No
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	No
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	Yes

General Product parameters

Energy consumption in on-mode (kWh/1000h)	72 k
Energy efficiency class	E
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	6351
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3500K
On-mode power (P_{on}), expressed in W [x,x]	71
Standby power (P_{sb}), expressed in W and rounded to the second decimal	
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	>80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	
Spectral power distribution in the range 250 nm to 800 nm, at full-load	



Claim of equivalent power (°)	
If yes, equivalent power (W)	
Chromaticity coordinates (x and y)	"x=0.4421 y=0.4081"

Parameters for directional light sources

Peak luminous intensity (cd)	
Beam angle in degrees, or the range of beam angles that can be set	
Beam Angle in degrees for directional light source	120

Parameters for LED and OLED light sources

R9 colour rendering index value	
Survival factor [x,xx]	
The lumen maintenance factor [x,xx]	
Displacement factor ($\cos \phi_1$)	
Colour consistency in McAdam ellipses	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage	
If yes then replacement claim (W)	
Flicker metric (Pst Lm) [x,x]	No
Stroboscopic effect metric (SVM) [X,X]	<0.9
Pon in W	70

