

Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	
Mains or non-mains [MLS/NMLS]	
Connected light source (CLS) [yes/no]	
Colour-tuneable light source [yes/no]	
Envelope [no/second/non-clear]	
High luminance light source [yes/no]	
Anti-glare shield [yes/no]	
Dimmable [yes/only with specific dimmers/no]	

General Product parameters

Energy consumption in on-mode (kWh/1000h)
Energy efficiency class
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :
On-mode power (P_{on}), expressed in W [x,x]
Standby power (P_{sb}), expressed in W and rounded to the second decimal
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):
Spectral power distribution in the range 250 nm to 800 nm, at full-load
Claim of equivalent power (c)
If yes, equivalent power (W)
Chromaticity coordinates (x and y)

Parameters for directional light sources

Peak luminous intensity (cd)
Beam angle in degrees, or the range of beam angles that can be set

Parameters for LED and OLED light sources

R9 colour rendering index value
Survival factor [x,xx]
The lumen maintenance factor [x,xx]
Displacement factor ($\cos \phi_1$)
Colour consistency in McAdam ellipses
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage
If yes then replacement claim (W)
Flicker metric (Pst Lm) [x,x]
Stroboscopic effect metric (SVM) [X,X]
Pon in W
Beam Angle in degrees for directional light source
Luminance -HLLS in cd/mm (only for HLLS)



NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE
Model identifier: 9030625
Type of light source: LED



Product information Sheet

General Information

Material number	9530625
Type	
Product segment	INDOOR

Dimensions

Diameter (in cm)	11.5 Cm
Width (in cm)	
Height (in cm)	115 Cm
Cut Out:	

Material & Colour

Enclosure Material	Aluminium
Colour	Sandy Black

Functionality

Switch Type	
Function	
Battery	
USB Charger	

Technical Information

Protection Degree	IP65
Protection Class	
Mains Voltage	100-240V
max. Wattage	2W
Lumen	181Lm
Equivalence With Incandescent Lamp (W)	
Colour Temperature	
Nominal Lifetime (in h)	
Switching Cycles	
Colour Rendering Index (Ra, CRI)	
Rated Lamp Power (0,1W precision)	
Colour Tolerance (LED, SDCM)	