

# NOVA LUCE

Supplier's name or trade mark: NOVA LUCE S.A  
Supplier's address: SCHIMATARI VIOTIAS 32009, GREECE  
Model identifier: 9180761  
Type of light source: LED



## Product information Sheet

### General Information

|                 |         |
|-----------------|---------|
| Material number | 9180761 |
| Type            | Pendant |
| Product segment | INDOOR  |

### Dimensions

|                |        |
|----------------|--------|
| Lenght (in cm) | 84cm   |
| Width (in cm)  | 77cm   |
| Height (in cm) | 25,5cm |
| Net Weight     |        |

### Material & Colour

|                    |                 |
|--------------------|-----------------|
| Enclosure Material | Metal & Acrylic |
| Colour             | Black           |
| Adjustable         | Yes             |

### Functionality

|             |          |
|-------------|----------|
| Switch Type |          |
| Function    | Dimmable |
| Battery     |          |
| USB Charger |          |

### Technical Information

|  |         |
|--|---------|
| Protection Degree                      | IP20    |
| Protection Class                       | CLASS I |
| Mains Voltage                          | 230V    |
| max. Wattage                           | 32W     |
| Lumen                                  | 2304Lm  |
| Equivalence With Incandescent Lamp (W) |         |
| Colour Temperature                     | 3000K   |
| Nominal Lifetime (in h)                | 30000H  |
| Switching Cycles                       | -       |
| Colour Rendering Index (Ra, CRI)       | 81,9    |
| Rated Lamp Power (0,1W precision)      | 32W     |
| Colour Tolerance (LED, SDCM)           | 2,4     |

## Product information

|   |      |
|---|------|
| Lighting technology used [LED/OLED/MIXED/OTHER] | LED  |
| Non-directional or directional [NDLS/DLS]       | NDLS |
| Mains or non-mains [MLS/NMLS]                   | NMLS |
| Connected light source (CLS) [yes/no]           | No   |
| Colour-tuneable light source [yes/no]           | No   |
| Envelope [no/second/non-clear]                  | -    |
| High luminance light source [yes/no]            | No   |
| Anti-glare shield [yes/no]                      | No   |
| Dimmable [yes/only with specific dimmers/no]    | Yes  |


## General Product parameters

|   |        |
|---|--------|
| Energy consumption in on-mode (kWh/1000h)   | 32.0   |
| Energy efficiency class   | G      |
| Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)              | 2304lm |
| Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set : | 3091K  |
| On-mode power ( $P_{on}$ ), expressed in W [x,x]  | 32W    |
| Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal  | 0      |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal   | 0      |
| Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set   | 81,9   |

Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):

"2835\*0.2W  
(4W+6W)\*6PCS"

Spectral power distribution in the range 250 nm to 800 nm, at full-load



## Parameters for LED and OLED light sources

|  |        |
|--|--------|
| R9 colour rendering index value  | 3      |
| Survival factor [x,xx]   | 0,9    |
| The lumen maintenance factor [x,xx]  | 96%    |
| Displacement factor ( $\cos \phi_1$ )  | 0,975  |
| Colour consistency in McAdam ellipses  | 2,4    |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular Wattage   |        |
| If yes then replacement claim (W)  |        |
| Flicker metric (Pst Lm) [x,x]  | 0,273  |
| Stroboscopic effect metric (SVM) [X,X]   | 0,253  |
| Pon in W   | 31.41W |
| Displacement factor ( $\cos \phi_1$ ) for LED and OLED mains light sources   | 0,967  |
| Colour consistency in MacAdam ellipse steps for LED and OLED light sources   | 2,4    |
| Flicker metric (PstLM) for LED and OLED light sources  | 0,273  |
| Stroboscopic effect metric (SVM) for LED and OLED light sources  | 0,253  |
| Excitation purity, only for CTLS, for the following colours and dominant wavelength within the given range: Blue 440nm - 490nm, Green 520nm - 570nm, Red 610nm - 670nm |        |

