

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Elstead Lighting

**Supplier's address:** Technical, Komandosów 3, 32-085 Modlniczka, PL

**Model identifier:** WELLAND-F-S-MOD

## Type of light source:

|                                                     |        |                                 |     |
|-----------------------------------------------------|--------|---------------------------------|-----|
| Lighting technology used:                           | LED    | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | Module |                                 |     |
| Mains or non-mains:                                 | MLS    | Connected light source (CLS):   | No  |
| Colour-tuneable light source:                       | No     | Envelope:                       | -   |
| High luminance light source:                        | No     |                                 |     |
| Anti-glare shield:                                  | No     | Dimmable:                       | No  |

## Product parameters


| Parameter                                                                                                                                      | Value                     | Parameter                                                                                                                                                  | Value                  |
|------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| <b>General product parameters:</b>                                                                                                             |                           |                                                                                                                                                            |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                  | 12                        | Energy efficiency class                                                                                                                                    | F                      |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 1 026 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000                  |
| On-mode power ( $P_{on}$ ), expressed in W                                                                                                     | 12,0                      | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal                                                                               | 0,00                   |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal                                                | -                         | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 80                     |
| Outer dimensions without separate control gear, lighting control                                                                               | Height                    | Spectral power distribution in the range 250 nm to 800 nm, at full-load                                                                                    | See image in last page |
|                                                                                                                                                | Width                     |                                                                                                                                                            |                        |
|                                                                                                                                                | Depth                     |                                                                                                                                                            |                        |

|                                                                                                                         |       |                                                                    |                |  |
|-------------------------------------------------------------------------------------------------------------------------|-------|--------------------------------------------------------------------|----------------|--|
| parts and non-lighting control parts, if any (millimetre)                                                               |       |                                                                    |                |  |
| Claim of equivalent power <sup>(a)</sup>                                                                                | -     | If yes, equivalent power (W)                                       | -              |  |
|                                                                                                                         |       | Chromaticity coordinates (x and y)                                 | 0,443<br>0,401 |  |
| <b>Parameters for directional light sources:</b>                                                                        |       |                                                                    |                |  |
| Peak luminous intensity (cd)                                                                                            | 1 026 | Beam angle in degrees, or the range of beam angles that can be set | 120            |  |
| <b>Parameters for LED and OLED light sources:</b>                                                                       |       |                                                                    |                |  |
| R9 colour rendering index value                                                                                         | 80    | Survival factor                                                    | 0,90           |  |
| the lumen maintenance factor                                                                                            | 0,90  |                                                                    |                |  |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                 |       |                                                                    |                |  |
| displacement factor (cos $\phi_1$ )                                                                                     | 0,10  | Colour consistency in McAdam ellipses                              | 6              |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b)  | If yes then replacement claim (W)                                  | -              |  |
| Flicker metric (Pst LM)                                                                                                 | 0,9   | Stroboscopic effect metric (SVM)                                   | 0,4            |  |

(a) '-': not applicable;

(b) '-': not applicable;

# 3000K



Model placed on the Union market from 23/03/2022



**EPREL registration number:** 1181870

<https://eprel.ec.europa.eu/qr/1181870>

**Supplier:** Elstead Lighting Sp. z o.o. (Importer)

**Website:** [www.elsteadlighting.pl](http://www.elsteadlighting.pl)

**Customer care service:**

**Name:** Technical

**Website:** <https://elsteadlighting.pl/>

**Email:** [technical@elsteadlighting.pl](mailto:technical@elsteadlighting.pl)

**Phone:** +48 12 444 10 91

**Address:**

Komandosów 3  
32-085 Modlniczka  
Poland